

PRODUCT SPECIFICATION

CoolPro[®] UPP
(Unreinforced)

1.0 STYLE

2.0 MATERIAL PROPERTIES

	<u>UPP60</u>	<u>UPP80</u>	<u>UPP100</u>
2.1 Thickness (±10%)	60 mil	80 mil	100 mil
2.3 Resin Type	← Polypropylene →		

3.0 MECHANICAL PROPERTIES

ASTM TEST METHODS

3.1 Tensile Strength	108 lbs/in	144 lbs/in	180 lbs/in	D6693
3.2 Tensile Elongation	700 %	700 %	700 %	D6693
3.3 Tear Resistance	24 lbs	30 lbs	43 lbs	D1004
3.4 Puncture Resistance	45 lbs	54 lbs	68 lbs	D4833
3.5 Dimensional Stability	±1 % max	±0.5 % max	±0.5 % max	D1204
3.6 Low Temperature	-40 °F	-40 °F	-40 °F	D2136
3.7 Stress Crack Resistance	3,000 hrs	3,000 hrs	3,000 hrs	D1693
3.8 UV Resistance (black)	35,000 hrs	35,000 hrs	35,000 hrs	G154
3.9 Ozone Resistance (100 ppm / 104°F / 7 days)	Pass	Pass	Pass	D1149

A variety of standard widths and colors are available including NSF 61 certified material. Contact Cooley Engineered Membranes for details.

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, No Warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.